
Understanding Hydrogeological Dynamics: Integrating Multiple Approaches at a Chalk Cliff Site in Normandy, France

Thomas Junique*¹, Raphaël Antoine¹, Cyrille Fauchard¹, Vincent Guilbert¹, Bruno Beaucamp¹, Cyril Ledun¹, Stéphane Costa², Olivier Maquaire², and Robert Davidson²

¹Centre d'Etudes et d'Expertise sur les Risques, l'Environnement, la Mobilité et l'Aménagement - Equipe-projet ENDSUM, Le Grand-Quevilly, France – GEGENAA EA 3795, Université de Reims Champagne-Ardenne, 2, esplanade Roland Garros, 51100 Reims – France

²Normandie Univ, UNICAEN, CNRS, IDEES, Caen, France – F-14000 – France

Résumé

Climate change-induced sea level rise presents significant challenges for coastal areas worldwide, especially for the densely populated regions located along the coast. The coastal areas of Normandy, France, are particularly vulnerable to sea level rise, with observed retreat speeds ranging from 0.09 to 0.80 m/y. This rise in sea levels leads to various problems, including coastal erosion and saltwater intrusion into freshwater aquifers, which has significant implications for agriculture, industry, drinking water supply, and biodiversity. Understanding the interactions between saltwater and freshwater is crucial for managing groundwater resources effectively.

Geophysical methods offer a non-invasive approach to assess the internal characteristics of geological formations. These methods provide valuable insights into stability and seawater intrusion without the need for costly drilling. A multidisciplinary study was conducted on a chalk cliff site in Sainte-Marguerite-sur-Mer, Normandy, combining optical and geophysical techniques. For optical methods, an unmanned aerial vehicle (UAV) equipped with visible infrared and thermal cameras, was used to obtain detailed photogrammetric models of the study area. For geophysical methods, Electrical Resistivity Imaging (ERI) was used to obtain a visualization of site resistivity. Two ERI profiles on cliff plateau, near and far from main scarp. Also, four transverse profiles start from plateau, cross cliff, reach rocky platform. Finally, a piezometer was equipped with instruments at two levels allowing continuous monitoring of the groundwater level, salinity and water temperature.

This study leads to the identification of several vulnerable areas prone to collapse and saltwater intrusion beneath different parts of the chalk cliff. The ERI profiles revealed conductive zones representing saline water intrusion at the base of the cliff, primarily observed in the southwestern part. Brackish water migration was also observed at the base of the cliff and the rocky platform, indicating haline convection driven by density differences. Additionally, the study found that areas of high resistivity at the top of the cliff corresponded to elevated temperatures detected by thermal infrared imaging. These anomalies are explained by air-flow drying the cracks, inducing a hot anomaly compared to the colder wet surroundings. Such areas can serve as indicators of unstable regions subject to future rockfalls.

*Intervenant

Mots-Clés: Saltwater intrusion, Geophysical methods, Chalk cliff